

**IE-C5DD4UG0800MCAXXX-X****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Assembled IE cables, PROFINET, Cat. 5, PUR, green, drag-chain compatible, M12

**General ordering data**

|            |   |
|------------|---|
| Version    | Dragline cable, PROFINET, M12 D-code – IP 67 angled pin, Open, Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B), PUR, 80 m |
| Order No.  | <a href="#">1059750800</a>  |
| Type       | IE-C5DD4UG0800MCAXXX-X  |
| GTIN (EAN) | 4050118849219   |
| Qty.       | 1 pc(s).  |

## IE-C5DD4UG0800MCAXXX-X

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |                |
|------------|---------|-----------------|----------------|
| Length     | 80 m    | Length (inches) | 3,149.606 inch |
| Net weight | 4,980 g |                 |                |

## Temperatures

|                     |                |                          |                |
|---------------------|----------------|--------------------------|----------------|
| Storage temperature | -50 °C...70 °C | Installation temperature | -20 °C...60 °C |
|---------------------|----------------|--------------------------|----------------|

## Cable specific standards

|                               |   |                              |                          |
|-------------------------------|---|------------------------------|--------------------------|
| Standard, insulating material | DIN EN 50290-2-23 (VDE 0819) Table 2/A (HD 624.3) | Standard, shielding material | DIN EN 13602 Cu-ETP-A..B |
| Standard, wire material       | DIN EN 13602 Cu-ETP-A                             |                              |                          |

## Standards

|                               |   |                              |                          |
|-------------------------------|---|------------------------------|--------------------------|
| Standard, insulating material | DIN EN 50290-2-23 (VDE 0819) Table 2/A (HD 624.3) | Standard, shielding material | DIN EN 13602 Cu-ETP-A..B |
| Standard, wire material       | DIN EN 13602 Cu-ETP-A                             |                              |                          |

## Cable structure

|                                |   |                                       |                                   |
|--------------------------------|---|---------------------------------------|-----------------------------------|
| Arrangement of wire cores      | Star-quad   | Colour sequence or wires - wire pairs | white, yellow, blue, orange       |
| Complete shielding             | Aluminium foil, Shielding braid made from copper wiring | Cross-section                         | 4*AWG 22/7 - 0.32 mm <sup>2</sup> |
| Diameter of inner sheathing    | 3.9 mm  | Filler                                | As central element                |
| Material sheath                | PUR   | Overlap of shielding braid            | 85 %                              |
| Sheath diameter, max.          | 6.7 mm  | Sheath diameter, min.                 | 6.3 mm                            |
| Sheathing colour               | green (RAL 6018)  | Sheathing material thickness          | 0.9 mm                            |
| Shielding                      | SF/UTP  | Shielding braid thickness             | 0.13 mm                           |
| Standard designations          | 2YH(ST)C11Y<br>2x2x0,75/1,5-100 LI VZN<br>GN FRNC       | Strands                               | 7                                 |
| Wire core insulation thickness | 0.38 mm   | Wire material                         | Stranded tin-plated copper wire   |

## Electrical properties of cable

|                          |                         |                                |   |
|--------------------------|-------------------------|--------------------------------|---|
| Capacity at 1 kHz        | 52 nF/km                | Category                       | Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B) |
| Characteristic impedance | 100 ± 15 Ω at 1–100 MHz | Delay skew                     | 40 ns/100m                                  |
| Loop resistance          | 120 Ω/km                | Operating voltage (UL rating)  | 600 V                                       |
| Operating voltage, UL    | 600 V                   | Resistance differential        | 3 %   |
| Speed                    | 180 m/min               | Test voltage: wire-wire-shield | 2000 V <sub>eff</sub> , 50 Hz, 1 min        |
| Transfer impedance       | 20 mΩ/m at 10 MHz       |                                |   |

## IE-C5DD4UG0800MCAXXX-X

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Mechanical and material properties of cable

|                                 |  |                                |                                |
|---------------------------------|--|--------------------------------|--------------------------------|
| Abrasion resistance             | very good                              | Acceleration                   | 4 m/s <sup>2</sup>             |
| Bending cycles                  | 3 Mio                                  | Fire propagation               | No                             |
| Halogen                         | halogen-free, according to IEC 60754-2 | Min. bending radius, once only | 5 x cable diameter             |
| Min. bending radius, repetitive | 7.5 x cable diameter                   | Pulling force                  | ≤ 150 N                        |
| Resistance to oils              | in accordance with IEC 60811-2-1       | Resistance to spread of flame  | in accordance with IEC 60332-1 |
| Silicone-free                   | Yes                                    | Speed                          | 180 m/min                      |

## Plug, left

|           |   |
|-----------|---|
| Plug left | M12, D-coded, IP67, male contact, angled 90°, plug, Plastic, shielded |
|-----------|---|

## Plug, right

|            |                    |
|------------|--------------------|
| Plug right | free conductor end |
|------------|--------------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002599    | ETIM 7.0    | EC002599    |
| ETIM 8.0    | EC002599    | ETIM 9.0    | EC002599    |
| ECLASS 9.0  | 27-06-03-08 | ECLASS 9.1  | 27-06-03-08 |
| ECLASS 10.0 | 27-06-03-08 | ECLASS 11.0 | 27-06-03-08 |
| ECLASS 12.0 | 27-06-03-08 | ECLASS 13.0 | 27-06-03-08 |

## Environmental Product Compliance

|            |                                      |
|------------|--------------------------------------|
| REACH SVHC | Lead 7439-92-1                       |
| SCIP       | 67cf1078-beca-4687-860b-dc475a6ec24a |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |

**IE-C5DD4UG0800MCAXXX-X**

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

|        |     |
|--------|-----|
|        | M12 |
| yellow | 1   |
| white  | 2   |
| orange | 3   |
| blue   | 4   |

**IE-C5DD4UG0800MCAXXX-X****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Blank**

TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are various different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the PrintJet CONNECT, plotter or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

**General ordering data**

|            |                            |  |
|------------|----------------------------|--|
| Type       | TM-I 18 MC NE WS           | Version                                |
| Order No.  | <a href="#">1718431044</a> | TM-I, Insert markers, 18 x 4 mm, white |
| GTIN (EAN) | 4008190349011              |  |
| Qty.       | 320 pc(s).                 |  |

## IE-C5DD4UG0800MCAXXX-X

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Screwty® cable gland tool



## The ideal tool for any application

Screwty® is the ideal, all-purpose tool for tightening all common sensor and actuator cables. Even difficult-to-reach round plugs are accessible using the Screwty®. A simple turning movement tightens and loosens the connectors without the need for excessive force. The Screwty® is a unique and global solution since it fits with most cables and plugs from other vendors (over 90 %). The Screwty® consists of a handle with a conventional 1/4" adapter. Thus it can be used for all sizes: for M12 and M8 round plug-in connectors, and for M12F and M8F customisable plugs and sockets, as well as for all M23 plugs and sockets.

## General ordering data

| Type       | SCREWTY- M12               | Version   | Packaging     |
|------------|----------------------------|---|---------------|
| Order No.  | <a href="#">1900000000</a> | Cable gland tool for moulded M12 lines            | Cardboard box |
| GTIN (EAN) | 4032248375868              |   |               |
| Qty.       | 1 pc(s).                   |   |               |
| Type       | SCREWTY SET                | Version   | Packaging     |
| Order No.  | <a href="#">1910000000</a> | Cable gland tool for M8, M12 lines and connectors | Cardboard box |
| GTIN (EAN) | 4032248436842              |   |               |
| Qty.       | 1 pc(s).                   |   |               |

## Screwty® cable gland tool with torque function



## The ideal tool for any application

Screwty® is the ideal, all-purpose tool for tightening all common sensor and actuator cables. Even difficult-to-reach round plugs are accessible using the Screwty®. A simple turning movement tightens and loosens the connectors without the need for excessive force. The Screwty® is a unique and global solution since it fits with most cables and plugs from other vendors (over 90 %). The Screwty® consists of a handle with a conventional 1/4" adapter. Thus it can be used for all sizes: for M12 and M8 round plug-in connectors, and for M12F and M8F customisable plugs and sockets, as well as for all M23 plugs and sockets.

## General ordering data

| Type       | SCREWTY SET -DM            | Version   | Packaging     |
|------------|----------------------------|---|---------------|
| Order No.  | <a href="#">1920000000</a> | Cable gland tool for M8, M12 lines and connectors | Cardboard box |
| GTIN (EAN) | 4032248436859              |   |               |
| Qty.       | 1 pc(s).                   |   |               |
| Type       | SCREWTY-M12-DM             | Version   | Packaging     |
| Order No.  | <a href="#">1900001000</a> | Cable gland tool for moulded M12 lines            | Cardboard box |
| GTIN (EAN) | 4032248436408              |   |               |
| Qty.       | 1 pc(s).                   |   |               |

## IE-C5DD4UG0800MCAXXX-X

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Tools



The CST with blue blade cartridge produces the best stripping results. The blue double-stage blade cartridge is particularly suited for Ethernet cables. It saves time and also ensures optimal stripping results.

## General ordering data

|            |                            |                            |
|------------|----------------------------|----------------------------|
| Type       | IE-CST                     | Version                    |
| Order No.  | <a href="#">9204350000</a> | Tools, Sheathing strippers |
| GTIN (EAN) | 4032248653072              |                            |
| Qty.       | 1 pc(s).                   |                            |

## Blank



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are various different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the PrintJet CONNECT, plotter or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

## General ordering data

|            |                            |  |
|------------|----------------------------|--|
| Type       | TM-I 12 MC NE WS           | Version                                |
| Order No.  | <a href="#">1718411044</a> | TM-I, Insert markers, 12 x 4 mm, white |
| GTIN (EAN) | 4008190348977              |  |
| Qty.       | 320 pc(s).                 |  |

**IE-C5DD4UG0800MCAXXX-X****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Tools**

Sheathing stripper for PVC cables

**General ordering data**

|            |                            |                            |
|------------|----------------------------|----------------------------|
| Type       | AM 12                      | Version                    |
| Order No.  | <a href="#">9030060000</a> | Tools, Sheathing strippers |
| GTIN (EAN) | 4008190337827              |                            |
| Qty.       | 1 pc(s).                   |                            |