

VT SF 4/21 MC SDR V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com



Similar to illustration

SlimFix are conductor and cable markers with a space-saving design. The markers can be fitted even after the conductor has been installed. They consist of halogen-free material and comply with flammability rating V0/V2. SlimFix is an acknowledged and accredited marker type for traffic engineering applications. The SF tool allows easy installation, even in case of small markers.

Advantages:

- Halogen-free material
- Flammability rating V0/V2
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor cross-section is larger than 16.0 mm²
- Markers in proven MultiCard format



General ordering data

| | |
|---------------------|--|
| Version | SlimFix, Conductor and cable markers, 3.6 - 6 mm, 21 x 5.7 mm, To customer specification |
| Order No. | 1789260000 |
| Type | VT SF 4/21 MC SDR V0 |
| GTIN (EAN) | 4032248209057 |
| Qty. | 48 pc(s). |
| compatible printer | 2715590000 2438520000 2438510000 |
| Alternative product | 1919050000 |

VT SF 4/21 MC SDR V0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Depth | 6.1 mm | Depth (inches) | 0.24 inch |
| Height | 21 mm | Height (inches) | 0.827 inch |
| Width | 5.7 mm | Width (inches) | 0.224 inch |
| Net weight | 0.458 g | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -50...120 °C |
|-----------------------------|--------------|

General data

| | | | |
|--------------------------------------|--|-----------|--|
| Advice label | Colour based on customer requirements (Please send M-Print PRO file) | | |
| Colour | To customer specification | | |
| Colour of printing | black | | |
| Halogen | No | | |
| Material | Polyamide 66 | | |
| Number of markers per combination | 1 MultiCard = Conductor and cable markers | | |
| Number of markers per packaging unit | Form of supply | MultiCard | |
| Operating temperature range | -50...120 °C | | |
| Operating temperature range, max. | 120 °C | | |
| Operating temperature range, min. | -50 °C | | |
| Orientation of print | horizontal | | |
| Printed characters | Based on customer requirements (Please send M-Print PRO file) | | |
| Printing method | MC Laser | | |
| Size of labelling field | 21 x 5.7 mm | | |
| Type of printing | To customer specification | | |
| UL 94 flammability rating | V-0 | | |
| Width | 5.7 mm | | |

Conductor and cable markers

| | | | |
|-------------------------------|---------------------|----------------------------------|-------------------------|
| Conductor O.D. | 3.6 - 6 mm | Conductor O.D., max. | 6 mm |
| Conductor O.D., min. | 3.6 mm | Conductor cross-section, max. | 4 mm ² |
| Conductor cross-section, min. | 2.5 mm ² | Cross-section for connected wire | 2.5 - 4 mm ² |
| Halogen | No | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ECLASS 9.0 | 27-40-04-01 | ECLASS 9.1 | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------|--|
| Catalogues | Catalogues in PDF-format |
|------------|--|