

**HV2700/3-M12 F****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The efficient and reliable distribution of electrical power in a challenging environment requires interface solutions that are optimally designed for the special characteristics of a particular application. Perfect interplay is what you get with our high-current terminal solutions combined with Klippon® Protect enclosures in a weather-proof design.

Our HV 2700 und HV 4000 high-voltage terminals provide you with a modular and scalable system which, thanks to the ring cable lug connection system, is a globally recognised and proven railway technology and easy to install anywhere in the world. The products are tested and comply with the requirements of the technical standards EN 50155, EN 50124-1, EN 45545 and IEC 61373. Our products are subject to ongoing product monitoring and development.

We have put together a small selection for you, but we are happy to configure a bespoke solution.

**Customised installation**

The challenges for the future are reducing costs and increasing efficiency. This requires intelligent, individual solutions which are tailored to your requirements. In our application spectrum we offer you a highly qualified customer-specific manufacturing service.

Whether you need modified products, pre-assembled terminal rails or complete small cabinets: we produce the solutions developed for your application quickly and flexibly.

**General ordering data**

Version	Bolt-type screw terminals, Feed-through terminal, Screw connection
Order No.	<a href="#">2540690000</a>
Type	HV2700/3-M12 F
GTIN (EAN)	4050118554373
Qty.	1 pc(s).

## HV2700/3-M12 F

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Depth	90 mm	Depth (inches)	3.543 inch
Height	220 mm	Height (inches)	8.661 inch
Width	240 mm	Width (inches)	9.449 inch
Diameter	11 mm	Mounting dimension - height	130 mm
Mounting dimension - width	215 mm	Net weight	4,800 g

## Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	140 °C
----------------------------------	--------	----------------------------------	--------

## Material data

Colour	red	UL 94 flammability rating	V-0
--------	-----	---------------------------	-----

## System specifications

End cover plate required	No	Number of levels	1
Number of clamping points per level	3	Levels cross-connected internally	Yes
Rail	Mounting plate		

## Additional technical data

Explosion-tested version	No
--------------------------	----

## Conductors for clamping (rated connection)

Cable lug to DIN 46234	10...185 mm <sup>2</sup>	Clamping range, bolted connection , max.	185 mm <sup>2</sup>
Clamping range, bolted connection , min.	10 mm <sup>2</sup>	Clamping range, max.	185 mm <sup>2</sup>
Clamping range, min.	10 mm <sup>2</sup>	Clamping screw	M 12
Connection cross-section, finely stranded, max.	185 mm <sup>2</sup>	Connection cross-section, finely stranded, min.	10 mm <sup>2</sup>
Connection direction	on side	Number of connections	6
Stud size for spade connection	M 12	Tightening torque, max.	35 Nm
Tightening torque, min.	33 Nm	Type of connection	Screw connection
Wire connection cross section, finely stranded, max.	185 mm <sup>2</sup>	Wire connection cross section, finely stranded, min.	10 mm <sup>2</sup>

## Dimensions

Diameter	11 mm
----------	-------

## General

Rail	Standards	EN 45545-2:2020, NFPA 130 ASTM E 162/ 662, BSS 7239/ 7242
Mounting plate		

**HV2700/3-M12 F****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Rating data**

Rated cross-section	185 mm <sup>2</sup>	Rated voltage	2,700 V
Voltage with epoxy resin partition plate	2,700 V	Rated current	600 A
Current at maximum wires	600 A	Standards	EN 45545-2:2020, NFPA 130 ASTM E 162/ 662, BSS 7239/ 7242
Rated impulse withstand voltage	25 kV	Impulse voltage with epoxy resin partition plate	25 kV
Pollution severity	3		

**Classifications**

ETIM 6.0	EC000897	ETIM 7.0	EC000897
ETIM 8.0	EC000897	ETIM 9.0	EC000897
ECLASS 9.0	27-14-11-20	ECLASS 9.1	27-14-11-20
ECLASS 10.0	27-14-11-20	ECLASS 11.0	27-14-11-20
ECLASS 12.0	27-14-11-20	ECLASS 13.0	27-25-01-01
ECLASS 14.0	27-25-01-01		

**Environmental Product Compliance**

REACH SVHC	/
RoHS Compliance Status	Compliant without exemption

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">CAD data – STEP</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>