

SCT-C 7.9/200**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

Cable ties are characterised by maximum tying force and a long life. Steel cable ties also offer permanent fastening under extreme conditions such as high temperatures or severe chemical effects.

- Fully coated stainless steel cable ties
- Secure ball locking mechanism for a fast and simple installation
- Can be attached manually or using a tool
- These cables ties are recommended for special applications, such as for use with saline spray, extreme temperatures or corrosive surroundings.

General ordering data

| | |
|------------|---|
| Version | Cable ties, 7.9 x 200 mm, Stainless steel, polyester coated, 1112 N |
| Order No. | 1015310000 |
| Type | SCT-C 7.9/200 |
| GTIN (EAN) | 4032248724284 |
| Qty. | 100 pc(s). |

SCT-C 7.9/200

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Depth | 0.26 mm | Depth (inches) | 0.01 inch |
| Height | 200 mm | Height (inches) | 7.874 inch |
| Width | 7.9 mm | Width (inches) | 0.311 inch |
| Net weight | 4.92 g | | |

Temperatures

| | | | |
|----------------------------------|--------------|----------------------------------|--------|
| Operating temperature range | -80...150 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 165 °C | | |

Installation materials

| | | | |
|-----------------------------------|---------|-----------------------------------|-----------------------------------|
| Bundle diameter, max. | 50 mm | Bundle diameter, min. | 20 mm |
| Cable diameter, max. | 50 mm | For re-opening | No |
| Halogen | No | Material | Stainless steel, polyester coated |
| Operating temperature range, max. | 150 °C | Operating temperature range, min. | -80 °C |
| Tensile strength | 1,112 N | Tensile strength (Pound-force) | 250 lbf |
| UV-resistant | No | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000046 | ETIM 7.0 | EC000046 |
| ETIM 8.0 | EC000046 | ETIM 9.0 | EC000046 |
| ECLASS 9.0 | 27-14-07-02 | ECLASS 9.1 | 27-14-07-02 |
| ECLASS 10.0 | 27-14-07-02 | ECLASS 11.0 | 27-14-07-02 |
| ECLASS 12.0 | 27-14-07-02 | ECLASS 13.0 | 27-14-07-02 |

Approvals

Approvals



| | |
|-------------------------|------------|
| ROHS | Conform |
| UL File Number Search | UL Website |
| Certificate no. (cULus) | E524836 |

Downloads

Catalogues [Catalogues in PDF-format](#)

SCT-C 7.9/200

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Drawing

