CMA-22-500-5A-5VA-0,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Do not use product for new developments



Similar to illustration

Plug-on current transformers
Plug-on current transformers are especially suitable for mounting on the busbar.
The advantages of this type are: screwless connection technology with tension clamp connection, time-saving connection option for solid and flexible conductors, shock-resistant and vibration-proof, high mechanical holding forces and high current resistance.

General ordering data

Version	Primary current: 500 A, Secondary current max.: 5 A, Load: 5 VA, Tolerance class: 0,5
Order No.	1482220000
Type	CMA-22-500-5A-5VA-0,5
GTIN (EAN)	4050118291254
Qty.	1 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2023-12-31
Alternative product	1482070000

Creation date March 28, 2024 8:14:19 PM CET

CMA-22-500-5A-5VA-0,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	75.5 mm	Depth (inches)	2.972 inch
Height	35 mm	Height (inches)	1.378 inch
Width	61 mm	Width (inches)	2.402 inch
Net weight	286 g		

Temperatures

Storage temperature	-40 °C...70 °C	Operating temperature	-5 °C...50 °C
Continuous operating temp., min.	-5 °C	Continuous operating temp., max.	50 °C

Dimensions of live conductors

Type of conductor	Insulated conductor only	Round conductor	25 mm
Rail	20 x 20 mm	Installation location	Indoor use

Electrical attributes

Load	5 VA	Primary conductor temperature	70 °C
Primary current	500 A	Secondary current	0...5 A
Tolerance class	0,5		

Classifications

ETIM 6.0	EC002048	ETIM 7.0	EC002048
ETIM 8.0	EC002048	ETIM 9.0	EC002048
ECLASS 9.0	27-21-09-02	ECLASS 9.1	27-21-09-02
ECLASS 10.0	27-21-09-02	ECLASS 11.0	27-21-09-02
ECLASS 12.0	27-21-09-02	ECLASS 13.0	27-21-09-02

Approvals

ROHS	Conform

Downloads

User Documentation	Instruction sheet
Catalogues	Catalogues in PDF-format

CMA-22-500-5A-5VA-0,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings





