

UC20-M4000**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

With u-control M3000, automation solutions can be perfectly integrated into the IoT. The powerful controller also works as an edge device for providing local information in the network and can be expanded by connecting function modules – ideal for automation and IIoT applications. u-control M4000 offers two additional CPU cores, two additional Ethernet interfaces and more RAM, NV RAM, and flash memory for complex edge computing in automation.

General ordering data

Version	Controller, IP20, AutomationController, CODESYS
Order No.	2839160000
Type	UC20-M4000
GTIN (EAN)	4064675446125
Qty.	1 pc(s).

UC20-M4000

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	101 mm	Depth (inches)	3.976 inch
Height	120 mm	Height (inches)	4.724 inch
Width	80 mm	Width (inches)	3.15 inch
Mounting dimension - height	120 mm	Net weight	250 g

Probability of failure

MTBF	According to Standard	MIL-HDBK-217-FN2
	Ambient temperature	50 °C

Connection data

Type of connection	PUSH IN	Wire connection cross section, finely stranded, max.	1.5 mm ²
Wire connection cross section, finely stranded, min.	0.14 mm ²	Wire cross-section, finely stranded, max. (AWG)	AWG 26
Wire cross-section, finely stranded, min. (AWG)	AWG 16	Wire cross-section, solid, max.	1.5 mm ²
Wire cross-section, solid, max. (AWG)	AWG 26	Wire cross-section, solid, min.	0.14 mm ²
Wire cross-section, solid, min. (AWG)	AWG 16		

General data

Air humidity (operation)	10% to 95%, non-condensing as per IEC 61131-2		
Air humidity (storage)	10% to 95%, non-condensing as per IEC 61131-2		
Air humidity (transport)	10% to 95%, non-condensing as per IEC 61131-2		
Air pressure (operation)	≥ 795 hPa as per IEC 61131-2		
Air pressure (storage)	≥ 700 hPa as per IEC 61131-2		
Air pressure (transport)	≥ 700 hPa as per IEC 61131-2		
Operating temperature installation dependent	Mounting position	horizontal	
	Operating altitude, max	2,000 m	
	Operating temperature	min.	-40 °C
		max.	70 °C
	Mounting position	vertical	
	Operating altitude, max	2,000 m	
	Operating temperature	min.	-40 °C
		max.	50 °C
	Mounting position	horizontal	
	Operating altitude, max	3,000 m	
	Operating temperature	min.	-40 °C
		max.	60 °C
	Mounting position	vertical	
	Operating altitude, max	3,000 m	
	Operating temperature	min.	-40 °C
		max.	50 °C
Rail	TS 35		
UL 94 flammability rating	V-0		

Power supply

Current consumption from I _{sys} , typ.	116 mA		
Feed current for I _{IN} (input current path)	max.	10 A	
	nominal	10 A	
	min.	0 A	

Creation date April 27, 2024 11:16:10 AM CEST

UC20-M4000

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Feed current for I_{IN} (input current path), 10 A max.

Feed current for I_{OUT} (output current path)	nominal	10 A
	max.	10 A
	min.	0 A

Feed current for I_{OUT} (output current path), max.

Supply voltage for outputs 24 V DC +20 %/ -15 %

Supply voltage system and inputs 24 V DC +20 %/ -15 %

System data

Configuration interface	USB-C (3.1), MicroSD CARD	Connection type	PUSH IN
Engineering tool	u-OS	Interface	2x Host (USB-A 2.0), 4x 1 Gbps (RJ45)
Memory (Flash)	16 GB	Processor	Quad Core ARM Cortex A53, 1200 MHz
Program data memory expansion possible	No	Program data memory size	4 GB
Programming environment	CODESYS	Real-time clock	Battery buffered
Type of program data memory	DDR4	Type of user data memory	eMMC
User data memory size	16 GB	max. number of modules	64

Classifications

ETIM 6.0	EC000236	ETIM 7.0	EC000236
ETIM 8.0	EC000236	ETIM 9.0	EC000236
ECLASS 9.0	27-24-22-07	ECLASS 9.1	27-24-22-07
ECLASS 10.0	27-24-22-07	ECLASS 11.0	27-24-22-07
ECLASS 12.0	27-24-22-07	ECLASS 13.0	27-24-22-07

Approvals

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate no. (cULusEX)	E223527

Downloads



Approval/Certificate/Document of Conformity	Declaration of Conformity
Engineering Data	Quick start guide – Modbus - Understanding Coils and Register Quick start guide – Function blocks for UR20-3EM-230V-AC CAD data – STEP
Product Change Notification	Release notes - u-OS App PROCON-WEB ES
Software	Runtime Software – Archived CODESYS Control SL for Weidmueller u-OS Package Compatibility information – Archived u-OS App CODESYS Control SL Runtime Runtime Software – u-OS App CODESYS Control SL Runtime Runtime Software – CODESYS Control SL for Weidmueller u-OS Package
User Documentation	u-control MX0000 Manual (English)
Catalogues	Catalogues in PDF-format

Creation date April 27, 2024 11:16:10 AM CEST

Catalogue status 20.04.2024 / We reserve the right to make technical changes.

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

Drawings



UC20-M4000**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Accessories****Accessories****System accessory**

Discover a wide range of accessories for your u-remote system - the ideal addition to make your applications even more efficient and flexible.

General ordering data

Type	UR20-EBK-ACC	Version
Order No.	1346610000	End bracket, ,
GTIN (EAN)	4050118151596	
Qty.	5 pc(s).	
Type	UR20-SM-ACC	Version
Order No.	1339920000	Cover, ,
GTIN (EAN)	4050118144727	
Qty.	20 pc(s).	

Custom printing**General ordering data**

Type	PM 2.7/2.6 MC SDR	Version
Order No.	1323700000	OMNIMATE Signal - series PM, Pusher markers, 2.7 x 2.6 mm, Pitch in
GTIN (EAN)	4050118126761	mm (P): 3.50 Weidmueller, To customer specification
Qty.	192 pc(s).	

UC20-M4000

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/8-11.5 MC NE WS	Version
Order No.	1341630000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4050118145946	Weidmueller, white
Qty.	500 pc(s).	

USB cable - USB A - USB C

Assembled IE cables



General ordering data

Type	IE-USB-A-C-2.0M	Version
Order No.	2838380020	USB cable, USB A, USB C, PVC, 2 m
GTIN (EAN)	4064675444329	
Qty.	1 pc(s).	

UC20-M4000

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Accessories

Blank



General ordering data

Type	PM 2.7/2.6 MC NE WS	Version
Order No.	1323710000	OMNIMATE Signal - series PM, Pusher markers, 2.7 x 2.6 mm, Pitch in
GTIN (EAN)	4050118126778	mm (P): 3.50 Weidmueller, white
Qty.	960 pc(s).	

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/8-11.5 MC SDR	Version
Order No.	1341610000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4050118146059	Weidmueller, To customer specification
Qty.	100 pc(s).	